



WindCube Ground-based Vertical Profiler Lidar



Features

- Measurement from 40 meters to over 300 meters
- Pulsed lidar technology
- 4 inclined beams and 1 vertical beam
- 45 W nominal power
- Remote monitoring through WindCube Insights
- Multiple communication channels (wired, cellular, satellite)
- Optional autonomous power kit

WindCube® is a ground-based vertical profiler Lidar that measures accurate wind data up to over 300 meters. It is equivalent to a very tall met mast, collecting wind speed, direction, vertical wind speed, and turbulence intensity data at 20 different heights with limited installation constraints and high operational safety.

Based on pulsed Doppler heterodyne laser principle, the WindCube sends a light pulse at a high frequency into the atmosphere and observes the signal backscattered by aerosols naturally present in the air. The time between the pulse and the detection of the backscattered signal is processed by the system thanks to the Doppler effect, and provides an accurate measure of the wind speed and direction.

Pulsed laser technology

Pulsed Lidars send laser pulses at a very high frequency. To avoid confusing time delays and distance, the Doppler shift is analyzed before the next laser pulse is emitted. Therefore, the probe distance, or height, only depends on the time it takes for a pulse to be received after it has been emitted.

Multiple heights are measured simultaneously, and spatial resolution is constant throughout the entire wind profile. Also, measurement is not affected by clouds, fog, high density of dust, or obstacles.

Thanks to a vertical beam, the lidar allows a direct measurement of the vertical wind speed, and improves the turbulence intensity (TI) assessment.

Remote monitoring

The web-based WindCube Insights platform enables remote monitoring and control of the WindCube vertical profiler. Wind speed data and carrier-to-noise ratio (CNR) are displayed live, and the platform also provides the possibility to configure measurement heights and communication with the Lidar.

Ease of installation and operations

The Lidar is easy to handle and install. A couple of hours is enough to fully set up the lidar and start measuring. It is compatible with autonomous power solutions (power pack, solar panels), and its robustness supports operations continuity.

Technical data

Operating environment

Warranty	3 years standard
Preventive maintenance	3 years cycle (factory or onsite maintenance)
Temperature range (1)	-30°C to +45°C / -22°F to 113°F (chamber conditions)
Maximum altitude	3000m (when equipped with DC-DC convertor)
Operating humidity	0 to 95% RH (non-condensing)
Environmental Protection	Designed for installation in many kinds of weather and environmental conditions IP66 and IP67 (Inner sub-assemblies) IP54 (Lidar Casing) Radiation +1000W/m ² at +45°C
Rain protection	Wiper
Marine atmosphere (Salt Atmosphere Compliance)	IEC 60068-2-52 (2017) – 120 hours
Shocks and vibration	ISTA/FEDEX 6B

1) Starting the system at low temperature (lower than -20°C) will require to have the WindCube equipped with an adapted protection

Mechanical specifications

Cube dimensions (L × W × H)	554 × 566 × 554 mm (21.81 × 22.28 × 21.81 in)
With feet and wiper	608 × 566 × 661 mm (23.94 × 22.28 × 26.02 in)
Weight	59kg (system only) 28kg (shipping case only) 91kg (total with accessories)

Electrical and optical

Power consumption (1)	45 W between -5°C and 30°C / 23°F and 86°F 110W below -5°C / 23°F 55W over 30°C / 86°F
LASER Safety Compliance	1M Class / EN 60825-1:2014

1) Nominal power consumption taken from an initial state of the WindCube at 15°C.

Compliance

Compliance marks (1)	CE, FCC, IC
----------------------	-------------

1) As verified on WindCube without Geofencing option

Measurement parameters

Measurement range (1)	40 ... > 300 m
Data sampling rate	1 Hz
Measuring distances	20 user-defined distances simultaneously
Radial Wind Speed range	-23m/s to +23m/s
Reconstructed Wind Speed range	0m/s to 49m/s
Reconstructed Wind Direction range	0 – 360°
Speed accuracy (2)	0.1 m/s
Wind speed	0 ... > 60 m/s
Speed uncertainty (2)	40 – 80m: 1.4% to 2.6% 80 – 120m: 0.6% to 1.4% 120 – 135m: 0.6% to 0.8%
Direction accuracy (2)	2°
Beam geometry	4 inclined beams at 28° and 1 vertical beam

1) Height from WindCube feet. Data availability depends on environmental factors such as visibility, type of aerosols and variation of refractive index in the atmosphere

2) For 10-min averages, as assessed by several 3rd parties on multiple WindCube devices or in 2020 according to IEC 61400-12-1 Ed.2. Uncertainty figures are Final Accuracy Class divided by $\sqrt{3}$

Data output

Output data	1 s / 1-, 2-, 5-, 10-minute averaged (user-defined) horizontal and vertical wind speed Standard deviation Direction CNR (carrier-to-noise ratio) GPS coordinates Data availability
Complex terrain measurements	FCR unlimited license
Data storage	120 GB industrial disk (over 5 years storage of all data) WindCube Insights secured cloud-based server
Data file format	RTD and STA (file), UTF-8 encoding
Communication	LAN, USB, 3G, or 4G router (router availability depends on the region/country), Modbus RTU (gateways available), Wi-Fi
Time synchronization	GPS, NTP

VAISALA

www.vaisala.com

Published by Vaisala | B212243EN-C © Vaisala 2021

All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. Any reproduction, transfer, distribution or storage of information contained in this document is strictly prohibited. All specifications – technical included – are subject to change without notice.